

# HISTOCORE PEGASUS PLUS

## DUAL RETORT TISSUE PROCESSOR

### TECHNICAL SPECIFICATIONS



#### Dimensions and weight specification

Overall size of device in operating mode (Width x Depth x Height)	804 x 715 x 1533 mm
Overall size serial packaging (Width x Depth x Height)	1040 x 1045 x 1480 mm
Empty weight (without accessories)	235 kg
Overall weight (with accessories)	315 kg
Device weight including packaging	300 kg

#### Retort

Capacity	Max. 2 x 200 cassettes
Temperature (paraffin)	Paraffin temperature selectable from 58°C to 85°C
Temperature (processing reagents)	Ambient temperature or 35°C to 65°C
Temperature (cleaning reagents)	35°C to 85°C
Filling vacuum	-60 kPa
Draining pressure	45 kPa
Retort lid heating	Yes

#### Paraffin containers

Number of paraffin baths	4
Capacity	Max. 3.9L per paraffin bath
Melting time	About 4.5 hours for pellets, 3.5 hours for PEGASUS Parablocks
Temperature settings range	Paraffin melting point setting: 50°C to 65°C Standby temperature setting: Paraffin Melting
Waste paraffin drain	By gravity

#### Capacities

Number of reagent containers	17 reagent bottles, 1 condensate bottle, max. 3.88L
Protocols	20 freely configurable protocols. 5 pre-installed protocols. 2 pre-installed xylene protocols consisting of up to 10 reagents and 3 paraffin processing steps. 2 pre-installed xylene-free protocols consisting of up to 8 reagents and 3 paraffin processing steps. – Time per protocol step: 0 - 5999 minutes. – Delay time: max. 1000 hours. 1 pre-installed cleaning protocol
Maximum throughput	Up to 400 cassettes can be processed simultaneously
Drip tray	>3.88L
Density Meter	Yes
Reagent management system	<ul style="list-style-type: none"> <li>• Processing protocol: Cassettes/Cycles/Days/Concentration</li> <li>• Cleaning protocol: Cycles/Days</li> </ul>
Hardware and Software	<ul style="list-style-type: none"> <li>• Color LCD touchscreen, 12 inches</li> <li>• User-friendly, intelligent and multi-lingual user interface</li> <li>• Three USB 2.0 ports, DC 5V</li> <li>• Alarm system with two alarm sockets (for local alarm and remote alarm: 30V DC, maximum 1A)</li> <li>• Smart error handling for specimen protection</li> </ul>
Backlighting for reagent cabinets	Yes
Expired reagent bottle visual cue	Yes
Paraffin Cleaning	Yes

Advancing Cancer Diagnostics  
Improving Lives



# HISTOCORE PEGASUS PLUS

## DUAL RETORT TISSUE PROCESSOR

### TECHNICAL SPECIFICATIONS

Electrical specifications	
Nominal supply voltage	100-120 VAC/220-240 VAC
Nominal supply frequencies	50/60Hz
Power consumption	100-120 VAC 15A Max.; 220-240 VAC 10A Max.
Other specifications	
CE	Approved
CSA	Approved
Access levels	<ul style="list-style-type: none"> <li>• Operator</li> <li>• Supervisor</li> <li>• Administrator</li> <li>• Service</li> <li>• Manufacturer</li> </ul>
Password status	<ul style="list-style-type: none"> <li>• Operator</li> <li>• Supervisor</li> <li>• Administrator</li> <li>• Service</li> <li>• Manufacturer</li> </ul>
Type of password	Alphanumeric, freely selectable
Environmental specification	
Operating altitude (meters above sea level) (min/max)	Up to a max. of 2250 m above sea level
Temperature (operation) (min/max)	+10°C to +35°C
Relative humidity (operation) (min/max)	Humidity 20% to 80% non-condensing
Temperature (transit) (min/max)	-29°C to +50°C
Temperature (storage) (min/max)	+5°C to +50°C
Relative humidity (transit)	Humidity 10% to 85%
Relative humidity (storage)	Humidity 10% to 85% non-condensing
Minimum distance to walls	80 mm
BTU	<ul style="list-style-type: none"> <li>• 100-120 V: maximum 6141.86 BTU/h (1800 J/s)</li> <li>• 220-240 V: maximum 8189.14 BTU/h (2400 J/s)</li> </ul>
Emissions and boundary conditions	
Overvoltage category to IEC 61010-1	Overvoltage installation category II
Pollution degree to IEC 61010-1	Pollution degree 2
Means of protection to IEC 61010-1	Class I
Degree of protection to IEC 60529	IP20
A-weighted noise level, measured at 1 m distance	<70dB(A)
EMC class	Class A

Advancing Cancer Diagnostics  
Improving Lives

**Leica**  
BIO SYSTEMS