THE BOND FAMILY

MAKE A DIFFERENCE



BOND-MAX

Lab friendly operation with a small footprint

- » Average 3.5 Hour TAT (IHC)
- » View reagents at a glance
- » Uses as few as 100 uL reagent per slide
- » Compact, benchtop design

BOND-III

workflows

- » Actionable visual management
- » Compact, floor model design
- » Highest throughput per square meter

High throughput for organized

- » Average 2.5 Hour TAT (IHC)

High productivity for adaptable workflows

- » Average 1.5 Hour² TAT (IHC)
- » Fully adaptable for batch, case, or single slide workflows

BOND-PRIME

- » Semi-permanent, self-cleaning ARC Covertile
- » 70 reagent capacity for uninterrupted staining
- single slide IHC TAT as fast as one hour.

THE FREEDOM TO DISCOVER



BOND RX^m

- » Highly flexible, small footprint
- » Average 3.5 Hour TAT (IHC)
- » Design your ideal protocol
- » Create your own detection system
- » Compact, benchtop design



BOND RX

- » Highly flexible, fast throughput
- » Average 2.5 Hour TAT (IHC)
- » Design your ideal protocol
- » Create your own detection system
- » Commercialize your discovery

RESEARCH USE ONLY. NOT FOR USE IN DIAGNOSTIC PROCEDURES

ALL BOND INSTRUMENTS HAVE THE TECHNOLOGIES AND FEATURES CUSTOMERS DEPEND ON

FOR IN VITRO DIAGNOSTIC USE

OUALITY

- » Liquid Level Sensing for real-time reagent inventory
- » Total Tissue Care with Covertile technology
- » Consistent, high-quality staining

EFFICIENCY

- » Separates hazardous and non-hazardous waste
- » Covertile technology uses minimal reagents, so it produces minimal waste
- » Refill bulk reagents and empty waste at any time



